

Corghi Tire Changers Corghi Parts & Accessories Corghi Tire Tools

Brake Lathes
Tire Changers
Tire Machines
Wheel
Balancers
Freon
Recovery
Repair Parts
Accessories

A 2010



AMMCO

Accu-turn

All Tool

Associated
Performance

CEMB

Coats

Corghi

General description

Reliability, unbeatable value for money and a wide range of models are the reasons for the popularity of the **Corghi A2010 which has been one of our most requested products since its launch.**

Operation is automatic, with pneumatic tilting column and 20" turntable, and it is ideal for mounting/demounting car, van and motorcycle tyres.

The pneumatic tilting column combined with the **665 mm height of the turntable** give maximum ease and speed of use during mounting/demounting.

The standard head is designed to **protect even the lightest rims**, using interchangeable plastic components for the inner surfaces contacting the rim during tyre mounting/demounting.

Furthermore, to protect the rim, plastic guards are **standard supply** for all parts which could damage the rim during tyre changing, such as the turntable clamps, the bead breaker shoe and bead lifting lever.

Components such as **higher profile clamps** and **interchangeable clamping zones** bear witness to

Envirotech

the attention paid to ergonomics, safety and operating costs.

Performance
Brake Lathes

Main characteristics

- **Automatic tyre changer with pneumatic tilting column and 20" turntable**
- Turntable height **665 mm**
- Sliding pads with **interchangeable clamping zones**
- **Higher profile clamps** for better interior/exterior wheel clamping
- Clamps completely protected inside and out with **plastic** protectors to avoid damaging light rims
- Turntable with double pneumatic cylinder for secure clamping of all rim types
- **Pneumatic tilting arm support column** featuring high torsional rigidity in all operating positions
- Telescopic horizontal arm for rapid head positioning to the rim
- **Simultaneous pneumatic locking** of the horizontal and vertical arms with automatic positioning of the head in the optimal work position
- Head with interchangeable plastic parts for **rim protection**
- Bead breaking unit with stainless steel pneumatic cylinder
- Fixed bead breaker pad
- **Standard supply plastic protectors** for the bead breaker shoe and bead lifting lever
- Complete with lubrication filter and pressure regulator
- Gun inflation (with pedal only on T.I. version)
- **Available with traditional inflation or T.I. bead seating/inflation system**
- Available in electric or pneumatic versions or the DV model with two-speed motor

RELS

Robinair

RTI

White

Wynn's

Rebuilt
Equipment

Technical data

turntable

inside clamping capacity 13" - 23"
outside clamping capacity 10" - 20"
max. tyre diameter 960 mm
max. tyre width 305 mm / 12"
n° clamps: 4
n° cylinders: 2
rotational torque 1200 Nm
rotational torque (DV model) 1000 Nm
rotational speed 8 rpm
rotational speed (DV model) 6 - 18 rpm
height 665 mm

bead breaker

max. opening 320 mm
shoe pressure 15500 N

tool

working range 10" - 22"
column: pneumatic tilting
head locking: pneumatic

power supply

electric 3-phase 230/400 V – 0.75 kW
electric 1-phase 110/230 V – 0.75 kW
electric 1-phase (DV model) 230 V – 0.55 kW
pneumatic on request

operating pressure 10 bar

weight

standard model 214 kg
T.I. version 224 kg

Can't find what
you are
looking for?
Call Us or
Email - We
probably have
it in stock.

Dallas
(972) 241-6404

Nationally
(800) 749-5990

Email
arch@autoess.com